
Concrete Line 106 | 162

design: 2017, Cezary Zadorożny



Model Concrete Line 106 | 162

Material Concrete | Steel

Finish Coloured concrete, stainless steel elements

Dimensions Concrete Line 106: L: 106 cm, H: 7,5 cm, D: 4 cm

Power supply 220-240V

Light Source 106: 18W LED; 162: 28 W LED, ~3000 K or ~4200 K (dimmable)

Ceiling rose Concrete linear with buil-in driver

Weight 106: 4kg; 162: 10kg

User Manual:

- Gently remove the packaging.
- Before starting the installation, check if the product is complete and contains all elements without any damage.
- Check if all cables have undamaged insulation of wires and conductors.
- If any damage occurred during transport, report it to the seller.
- Turn off the power in the room where the lamp will be installed. Switch off the circuit breakers or the main power switch.
- It is recommended that the fixture be installed by an electrician or a properly trained person.
- The manufacturer does not provide wall plugs with the lamp. It is recommended to purchase plugs specifically designed for the mounting surface.
- Use only recommended bulbs to avoid overheating.
- It is recommended to install with gloves.

Maintenance Tips:

- Use a soft, dry, or slightly damp cloth to wipe off dust.
- Do not use any aggressive cleaning agents, as this may cause permanent stains or discoloration of the lamp.
- Keep the user manual.





Concrete Line 162: L: 162 cm, H: 7,5 cm, D: 4 cm

Concrete Line 106 | 162 design: 2017, Cezary Zadorożny

Model	Concrete Line 106 162
EAN code	106: 5902730884576 ; 162: 5902730885733
Producer	LOFTLIGHT Bottonova Sp. z o. o.
Design	Cezary Zadorożny
Туре	Pendant lamp
Materials	Concrete Steel
Finish	Coloured concrete, stainless steel elements
Length	106 cm 162 cm
Height	7,5 cm
Depth	4 cm
Standard cables length	120 cm
Power supply	220-240V
Light source	106: 18W LED; 162: 28 W LED (dimmable)
Light colour	~3000 K or ~4200 K
Color Rendering Index	95 Ra
Light stream	160: 1800 lm; 162: 2800lm
Ceiling rose	Concrete linear with buil-in driver
Number of light points	1
Weight	106: 4kg; 162: 10kg
IP protection degree	IP20





